

ELATION® WW PROFILE HP IP™
DMX Channel Values / Functions (8 Total DMX Channels)

Specifications are subject to change without any prior written notice.

Supports Software Versions: ≥ 1.0.0

MODE / CHANNEL			VALUE	FUNCTION
3CH	6CH	8CH		
1	1	1	0-255	LED INTENSITY Intensity 0 to 100%
N/A	N/A	2	0-255	LED FINE INTENSITY FINE Intensity Adjustment
2	2	3	0-127	GOBO ROTATOR GOBO Indexing
			128-189	Clockwise Rotation FAST to SLOW
			190-193	NO Rotation
			194-255	Counter-Clockwise Rotation SLOW to FAST
N/A	3	4	0-31	STROBE LED OFF
			32-63	LED ON
			64-95	Strobe Effect SLOW to FAST
			96-127	LED ON
			128-159	Pulse Effect In Sequences
			160-191	LED ON
			192-223	Random Strobe Effect SLOW to FAST
			224-255	LED ON
N/A	4	5	0-255	DIMMER Dimmer 0 to 100%
N/A	N/A	6	0-255	DIMMER FINE Dimmer FINE Adjustment
N/A	5	7	0-20	DIMMING CURVES STANDARD
			21-40	STAGE
			41-60	TV
			61-80	ARCHITECTURAL
			81-100	THEATRE
			101-255	Default to Unit Dimming Curve Setting
3	6	8	0-79	SPECIAL CONTROL Normal
			80-84	ALL Motor Reset
			85-87	NO Function
			88-90	Engage Scene By Input
			91-93	NO Function
			94-96	Store Scene 1 into Internal Memory
			97-99	NO Function
			100-119	Internal Program 1 (Scene 1~8)
			120-139	Internal Program 2 (Scene 9~16)
			140-159	Internal Program 3 (Scene 17~24)
			160-179	Internal Program 4 (Scene 25~32)
			180-199	Internal Program 5 (Scene 33~40)
			200-219	Internal Program 6 (Scene 41~48)
			220-239	Internal Program 7 (Scene 49~56)
240-255	NO Function			

ELATION | WW PROFILE HP IP™ | dmx traits

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu