



## **SPECIFICATIONS**

Pixel Pitch: 2.6mm

Physical Density: 123,904 (dots/m2)

**LED Type: SMD Chip** LED Size: SMD1515

Module Size: 250 x 250mm Module Resolution: 88 x 88 pixels **Drive Mode: Constant Current Drive** 

Horizontal and Vertical View Angle: H:140° | V:120°

Scan Way: 1/22

Cabinet Size: 500 x 500mm

Cabinet Resolution: 176 x 176 pixels Cabinet Weight:  $\geq 19.8$  lbs. ( $\geq 9.0$  kg) Cabinet Material: Die Cast Aluminum Alloy Brightness: 1200 (cd/m2) (after calibration)

Gray Scale: 14bit

Refresh Rate: Variable Up To 3840Hz Input Voltage: AC110V-220V, 50/60Hz Cabinet Max Power Consumption: 135W

Cabinet Average Max Power Consumption: 65W

**Protection Level: IP20** 

Environment: Indoors | -20° - 40° C | 10 - 90% RH

Life Span:  $\geq$ 50,000 Hours

## **OPTIONAL ACCESSORIES**

**EVH120 -** EVHD Series Rear Support Bracket - Install Version

EVH254 - EVHD Series Single Panel Rigging Bar

**EVH270 -** EVHD Series Rear Support Bracket - Quick Rig Version **EVH120 -** EVHD Series Rear Support Bracket - Install Version

EVH286 - EVHD Series 8 Panel Transport Case Specifications are subject to change without notice ©Elation Professional 08/16/17



## SPECIAL ORDER ITEM

## EVHD2™ SKU# EVH228

The EVHD2™ is a 2.6mm pixel pitch black face LED display. It's light weight durable diecast aluminum frame and modular front maintenance design, allows for easy installation and service. Features include a seamless bezelfree design, no fan metal cooling structure, and excellent color uniformity and brightness. The EVHD2™ is ideal for any broadcast installations.

