

**ELATION® DW PAR Z19 IP™**  
**DMX Channel Values / Functions (7 Total Channels)**

Features are subject to change without any prior written notice.

DMX CHANNEL MODE						VALUE	FUNCTION
02CH	03CH DW	03CH	05CH	06CH	07CH		
1	1					0-255	<b>DYNAMIC WHITE - All LEDs</b> 2,700K - 6,000K (0=Black - 255=100%)
		1	1	1	1	0-255	<b>COOL WHITE - All LEDs</b> Cool White (0=Black - 255=100%)
		2	2	2	2	0-255	<b>WARM WHITE - All LEDs</b> Warm White (0=Black - 255=100%)
					3		<b>SHUTTER / STROBE</b>
						0-31	NO Function
						32-95	Variable Strobe Effect SLOW to FAST
						96-127	LEDs ON
						128-159	Pulse Effect In Sequence SLOW to FAST
						160-191	LEDs ON
						192-223	Random Strobe Effect SLOW to FAST
						224-255	LEDs ON
			3	3	4	0-255	<b>MASTER DIMMER</b> 0 to 100%
			4	4	5	0-255	<b>MASTER DIMMER FINE (16 bit)</b> 0 to 100%
2	2	3	5	5	6	0-255	<b>ZOOM</b> Zoom 0% (5 Degrees) to 100% (45 Degrees)
	3			6	7		<b>DIMMING CURVE MODES</b>
		0-20	STANDARD				
		21-40	STAGE				
		41-60	TV				
		61-80	ARCHITECTURAL				
		81-100	THEATRE				
		101-255	Default to Unit Setting				

**ELATION** | DW PAR Z19 IP™ | dmx traits

**Elation Professional USA** | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | [www.elationlighting.com](http://www.elationlighting.com) | [info@elationlighting.com](mailto:info@elationlighting.com)

**Elation Professional B.V.** | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | [www.elationlighting.eu](http://www.elationlighting.eu) | [info@elationlighting.eu](mailto:info@elationlighting.eu)