



## EPT6IP™

SKU# **EPT600** PRELIMINARY SPECIFICATIONS

The new EPT6IP™ is a new 6mm pixel pitch modular outdoor rated Pro Touring LED display. It's light weight durable die-cast aluminum frame and (4) piece modular design, allows for easy installation and service. The EPT6IP™ uses the latest dot correction technology which provides full color uniformity and brightness. The EPT6IP™ is ideal for outdoor Pro Touring portable installations.

### SPECIFICATIONS

**Pixel Pitch:** 6.67mm  
**Physical Density:** 22,500(dots/m2)  
**LED Configuration:** 1R1G1B  
**LED Type:** SMD2828  
**Module Size:** 320x320mm  
**Module resolution:** 48x48  
**Drive Model:** MBI5151  
**Scanning Mode:** 1/6  
**Horizontal and Vertical View angle:** 120°  
**Brightness:** 5000cd/m2  
**Gray Scale:** 14bit  
**Refresh rate:** 1920Hz  
**Cabinet Resolution:** 96x96  
**Cabinet Max Power Consumption:** 252W  
**Cabinet Average Power Consumption:** 101W  
**Cabinet Size:** 640x640mm  
**Cabinet Weight:** 38.6 lbs. (17.5kg)  
**Cabinet Material:** Aluminum  
**Input Voltage:** AC110V220V +/-10%, 50/60Hz  
**Life Span:** 100,000 Hour  
**Protection Level:** IP65  
**Calibration Module**

